

OSX-666T

Weather Resistant PA Wall Speaker

Reliable IP-66 rated, weather resistant plastic cabinet wall speaker with outstanding sound clarity. Suitable for both indoor and outdoor use. Suitable for use on 100V line, or on direct 8Ω impedance.

- Comprises of a Polypropylene Cone Woofer, a Titanium Silk Dome Tweeter and a Crossover Network.
- Power taps can be selected through a slotted rotary switch knob at the rear, accessible after removing the terminal cover.
- 'U' type metal bracket for firm mounting and optimum positioning of the wall speaker.
- Bidirectional key holes in the mounting bracket are available for fixing the speaker horizontally or vertically.
- Use of Cable Gland, supplied along with, is essential for ensuring the IP rating of this speaker.
- Front grill is made of perforated aluminium sheet which provides rust-free service in various weather conditions. It is therefore advisable that OSX-666T should never be placed or stored with its front grill facing down. This may cause irreversible dent/depression in the grill.

SPECIFICATIONS

SPL at 1kHz (1W/1m)

POWER RATING 60W/8Ω; 30W/100V POWER TAPS ON 100V 30/15/7.5W **FREQUENCY RESPONSE** 95-20,000Hz

87dB Woofer 163mm (61/2"), Tweeter 25mm (1.0") **SPEAKER**

DIMENSIONS $W205 \times H330 \times D199 \, mm$

WEIGHT 1.31kg









Design and Specifications are subject to change without notice owing to continuous product up-gradation. Technical specifications are subject to production tolerances. We cannot be held responsible for printing errors, should they occur.

BELLINE TO BE

AHUJA RADIOS